



Safety Data Sheet Spetec PUR GT350

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name Spetec GT350

Relevant identified uses of the substance or mixture and uses advised against:

/

Concentration in use: /

Supplier's details

Name Alchemy-Spetec
Address 4508 Bibb Blvd
Tucker, GA 30084
Telephone (404) 618-0438

Emergency phone number(s)

Call CHEMTREC Day or Night
1-800-424-9300 / +1 703-527-3887

SECTION 2: Hazards identification:

Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

**EUH208 H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H334 Resp. Sens. 1 H351 Carc. 2
H373i STOT RE 2**

Label elements:**Pictograms:**

Signal word: Danger

Safety Data Sheet

Spetec PUR GT350

Hazard statements:

| | |
|----------------------------|---|
| EUH208: | Contains (diphenylmethane-4,4'-diisocyanate). May produce an allergic reaction. |
| H315 Skin Irrit. 2: | Causes skin irritation. |
| H317 Skin Sens. 1: | May cause an allergic skin reaction. |
| H319 Eye Irrit. 2: | Causes serious eye irritation. |
| H334 Resp. Sens. 1: | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H351 Carc. 2: | Suspected of causing cancer. |
| H373i STOT RE 2: | May cause damage to organs through prolonged or repeated exposure. |

Precautionary statements:

| | |
|------------------------|--|
| P261: | Avoid breathing dust/vapours/spray. |
| P280: | Wear protective gloves, protective clothing, eye protection, face protection. |
| P302+P352: | IF ON SKIN: Wash with plenty of soap and water. |
| P305+P351+P338: | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P342+P311: | If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. |
| P362+P364: | Take off contaminated clothing and wash it before reuse. |

Contains:

diphenylmethane-4,4'-diisocyanate

Other hazards:

None

SECTION 3: Composition/information on ingredients:

| | | |
|-----------------------------------|-----------|---|
| Propylene carbonate | > 30% | CAS number: 108-32-7 EINECS: 203-572-1 REACH Registration number: 01-2119537232-48 CLP Classification: H319 Eye Irrit. 2 |
| diphenylmethane-4,4'-diisocyanate | 15% - 30% | CAS number: 101-68-8 EINECS: 202-966-0 REACH Registration number: 01-2119457014-47 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1 H319 Eye Irrit. 2 H332 Acute tox. 4 H334 Resp. Sens. 1 H335i STOT SE 3 H351 Carc. 2 H373i STOT RE 2 |

For the full text of the H & R phrases mentioned in this section, see section 16.

SECTION 4: First aid measures:

Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

| | |
|----------------------|--|
| Skin contact: | remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital. |
| Eye contact: | first prolonged rinsing with water (contact lenses to be removed if this is easily done) then take to physician. |
| Ingestion: | rinse mouth, do not induce vomiting, take to hospital immediately. |
| Inhalation: | let sit upright, fresh air, rest and take to hospital. |

Most important symptoms and effects, both acute and delayed:

| | |
|----------------------|--|
| Skin contact: | redness, pain |
| Eye contact: | redness, pain, bad looking |
| Ingestion: | caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach |
| Inhalation: | headache, dizziness, nausea, drowsiness, unconsciousness |

Indication of any immediate medical attention and special treatment needed:

none

SECTION 5: Fire-fighting measures:

| | |
|---|----------------------------------|
| Extinguishing media: | CO2, foam, powder, sprayed water |
| Special hazards arising from the substance or mixture: | none |
| Advice for fire-fighters: | |
| Extinguishing agents to be avoided: | none |

SECTION 6: Accidental release measures:

| | |
|---|--|
| Personal precautions, protective equipment and emergency procedures: | Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely. |
| Environmental precautions: | do not allow to flow into sewers or open water. |
| Methods and material for containment and cleaning up: | remove by using absorbent material. |
| Reference to other sections: | for further information check sections 8 & 13. |

SECTION 7: Handling and storage:

Precautions for safe handling: handle with care to avoid spillage.

Conditions for safe storage, including any incompatibilities: keep in a sealed container in a closed, frost-free, ventilated room.

Specific end use(s): /

SECTION 8: Exposure controls/personal protection:

Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

/

Exposure controls:

| | | |
|------------------------|--|---|
| Inhalation protection: | if necessary, use an air-purifying face mask in case of respiratory hazards. |  |
| Skin protection: | handling with Viton-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands. |  |
| Eye protection: | keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems. |  |
| Other protection: | impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question. |  |

SECTION 9: Physical and chemical properties:

Information on basic physical and chemical properties:

Melting point/melting range: /

Boiling point/Boiling range: 242 °C — 242 °C

pH: /

pH 1% diluted in water: /

Vapour pressure/20°C,: 3 Pa

Vapour density: not applicable

Relative density, 20°C: 1.200 kg/l

Appearance/20°C: liquid

Flash point: 202 °C

Flammability (solid, gas): not applicable

Safety Data Sheet

Spetec PUR GT350

| | |
|---|----------------|
| Auto-ignition temperature: | / |
| Upper flammability or explosive limit, (Vol %): | / |
| Lower flammability or explosive limit, (Vol %): | / |
| Explosive properties: | not applicable |
| Oxidising properties: | not applicable |
| Decomposition temperature: | / |
| Solubility in water: | not soluble |
| Partition coefficient: n- octanol/water: | not applicable |
| Odour: | characteristic |
| Odour threshold: | not applicable |
| Dynamic viscosity, 20°C: | / |
| Kinematic viscosity, 20°C: | / |
| Evaporation rate (n-BuAc = 1): | / |

Other information:

| | |
|-----------------------------------|-------------|
| Volatile organic component (VOC): | / |
| Volatile organic component (VOC): | 582.000 g/l |

SECTION 10: Stability and reactivity:

| | |
|--|---|
| Reactivity: | stable under normal conditions. |
| Chemical stability: | extremely high or low temperatures. |
| Possibility of hazardous reactions: | None |
| Conditions to avoid: | protect from sunlight and do not expose to temperatures exceeding + 50°C. |
| Incompatible materials: | alkalines, water, acids, organic matter, oxidants, reductants |
| Hazardous decomposition products: | doesn't decompose with normal use |

SECTION 11: Toxicological information:

Information on toxicological effects:

| | |
|---|--|
| H315 Skin Irrit. 2: | Causes skin irritation. |
| H317 Skin Sens. 1: | May cause an allergic skin reaction. |
| H319 Eye Irrit. 2: | Causes serious eye irritation. |
| H334 Resp. Sens. 1: | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H351 Carc. 2: | Suspected of causing cancer. |
| H373i STOT RE 2: | May cause damage to organs through prolonged or repeated exposure. |
| Calculated acute toxicity, ATE oral: | / |
| Calculated acute toxicity, ATE dermal: | / |

Safety Data Sheet
Spetec PUR GT350

| | | |
|-----------------------------------|--|---|
| Propylene carbonate | LD50 oral, rat: dermal, rabbit: Inhalation, rat, 4h: ≥ 50 mg/l | ≥ 5,000 mg/kg LD50 ≥ 5,000 mg/kg LC50, |
| diphenylmethane-4,4'-diisocyanate | LD50 oral, rat: dermal, rabbit: Inhalation, rat, 4h: 11 mg/l | ≥ 5,000 mg/kg LD50 ≥ 5,000 mg/kg LC50, |

SECTION 12: Ecological information:

Toxicity:

| | | |
|---------------------|--|---|
| Propylene carbonate | LC50 (Fish): NOEC (Fish): EC50 (Daphnia): EC50 (Algae): NOEC (Algae): EC50 (soil microorganisms): | > 1000 mg/L (96h) 1000 mg/L (96h) > 1000 mg/L (24h) > 900 mg/L (72h) 900 mg/L (72h) 25619 mg/L (16h) |
|---------------------|--|---|

Persistence and degradability: No additional data available

Bioaccumulative potential: No additional data available

Mobility in soil:

Water hazard class, WGK: 1
Solubility in water: not soluble

Results of PBT and vPvB assessment: No additional data available

Other adverse effects: No additional data available

SECTION 13: Disposal considerations:

Waste treatment methods: Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

SECTION 14: Transport information:

UN number: not applicable
UN proper shipping name: ADR, IMDG, ICAO/IATA not applicable
Transport hazard class(es):
 Class(es): not applicable
 Identification number of the hazard: not applicable
Packing group: not applicable
Environmental hazards: not dangerous to the environment
Special precautions for user:
 Hazard characteristics: not applicable
 Additional guidance: not applicable

SECTION 15: Regulatory information:

Safety, health and environmental regulations/legislation specific for the substance or mixture:

| | |
|---|-------------------|
| Water hazard class, WGK: | 1 |
| Volatile organic component (VOC): | / |
| Volatile organic component (VOC): | 582.000 g/l |
| Composition by regulation (EC) 648/2004: | None |
| Chemical Safety Assessment: | No data available |

SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

| | |
|----------------|---|
| ADR: | Accord européen relatif au transport international des marchandises Dangereuses par Route |
| BCF: | Bioconcentration factor |
| CAS: | Chemical Abstracts Service |
| CLP: | Classification, Labelling and Packaging of chemicals |
| EINECS: | European INventory of Existing Commercial chemical Substances |
| Nr.: | number |
| PTB: | persistent, toxic, bioaccumulative |
| TLV: | Threshold Limit Value |
| vPvB: | very persistent and very bioaccumulative substances |
| WGK: | Water hazard class |
| WGK 1: | slightly hazardous for water |
| WGK 2: | hazardous for water |
| WGK 3: | extremely hazardous for water |

Legend to the R & H Phrases used in the safety data sheet:

EUH208: Contains (diphenylmethane-4,4'-diisocyanate). May produce an allergic reaction. **H315 Skin Irrit. 2:** Causes skin irritation. **H317 Skin Sens. 1:** May cause an allergic skin reaction. **H319 Eye Irrit. 2:** Causes serious eye irritation. **H332 Acute tox. 4:** Harmful if inhaled. **H334 Resp. Sens. 1:** May cause allergy or asthma symptoms or breathing difficulties if inhaled. **H335i STOT SE 3:** May cause respiratory irritation. **H351 Carc. 2:** Suspected of causing cancer. **H373i STOT RE 2:** May cause damage to organs through prolonged or repeated exposure.

Reason of revision, changes of following items:

not applicable

MSDS reference number:

ECM-108854,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.

Safety Data Sheet

Spetec PUR GT350

Further Information/Disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Alchemy-Spetec be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Alchemy-Spetec has been advised of the possibility of such damages.